

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Name: Anhydrous Ammonia

CAS No: 7664-41-7

Synonyms: Liquid Ammonia, Ammonia

US DOT STCC: 4904210

TDG STCC: 4920359

REACH Registration Number: 01-2119488876-14-0122

1.2. Intended Use of the Product

Fertilizers, Manufacture of Chemicals, Manufacture of synthetic fibers, Refrigerant, Cleaning solutions

1.3. Name, Address, and Telephone of the Responsible Party

Company

CF Industries Sales, LLC

4 Parkway North, Suite 400

Deerfield, Illinois 60015-2590

847-405-2400

www.cfindustries.com

1.4. Emergency Telephone Number

Emergency Number : 800-424-9300

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call CHEMTREC – Day or Night

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Flam. Gas 2	H221
Liquefied gas	H280
Acute Tox. 3 (Inhalation: gas)	H331
Skin Corr. 1B	H314
Eye Dam. 1	H318
STOT SE 3	H335
Aquatic Acute 1	H400
Aquatic Chronic 2	H411
Full text of H-phrases: see section 16	

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H221 - Flammable gas.
 H280 - Contains gas under pressure; may explode if heated.
 H314 - Causes severe skin burns and eye damage.
 H318 - Causes serious eye damage.
 H331 - Toxic if inhaled.
 H335 - May cause respiratory irritation.
 H400 - Very toxic to aquatic life.
 H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.
 P260 - Do not breathe mist, spray, vapors, gas.
 P261 - Avoid breathing vapors, mist, or spray.

Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center or doctor.
P311 - Call a poison center or doctor.
P312 - Call a poison center or doctor if you feel unwell.
P321 - Specific treatment (see Section 4 on this SDS).
P363 - Wash contaminated clothing before reuse.
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 - Eliminate all ignition sources if safe to do so.
P391 - Collect spillage.
P403 - Store in a well-ventilated place.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Ammonium hydroxide is very volatile and may release anhydrous ammonia as a gas. Ammonia vapor, in concentrations of 16-25% volume by weight in air, is flammable, toxic by inhalation and corrosive. Take all appropriate precautions.

2.4. Unknown Acute Toxicity (GHS-US) No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Ammonia	(CAS No) 7664-41-7	>99.5	Flam. Gas 2, H221 Liquefied gas, H280 Acute Tox. 3 (Inhalation: gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Ammonium hydroxide	(CAS No) 1336-21-6	<0.5	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400

3.2. Mixture

Not applicable

Full text of H-phrases: see section 16

Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Immediately call a POISON CENTER or doctor/physician.

Skin Contact: Immediately flush skin with plenty of water for at least 60 minutes. Remove contaminated clothing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Toxic if inhaled. Corrosive to eyes, respiratory system and skin.

Inhalation: Toxic if inhaled.

Skin Contact: Corrosive. Causes burns. Symptoms may include: Redness. Pain. Serious skin burns. Blisters.

Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva. Redness. Pain. Blurred vision. Severe burns.

Ingestion: Ingestion is an unlikely route of exposure for a gas.

Chronic Symptoms: Not available

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire. Do not use water directly on liquid ammonia as this will increase formation of ammonia vapors.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable gas. Ammonia concentrations in the range of 16-25% by volume in air can be ignited if heated to the auto-ignition temperature. Oil or other combustible materials increases the fire hazard.

Explosion Hazard: Forms explosive compounds with calcium hypochlorite, bleaches, gold, mercury, silver, chlorine and other halogens.

Reactivity: Corrosive to copper and aluminum, including their alloys, and galvanized surfaces.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Do not allow ammonia vapors to accumulate in confined areas where ignition may occur.

Firefighting Instructions: Stop leak if safe to do so. For a serious leak, use fire hose with fog nozzle and plant of water to absorb ammonia vapors. Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Move undamaged containers from immediate hazard area if it can be done with minimal risk. Water spray may be useful in minimizing or dispersing vapors and to protect persons shutting off flow. Cool equipment exposed to fire with water, if it can be done with minimal risk. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. Firefighters must use full bunker gear including NIOSH-approved positive-pressure self-contained breathing apparatus to protect against potential hazardous combustion and decomposition products.

Hazardous Combustion Products: Nitrogen oxides.

Other Information: Compressed gas or refrigerated liquid. Intense heating particularly in contact with hot metallic surfaces may cause decomposition of ammonia generating hydrogen, a flammable gas. Note that many materials, particularly plastics, become brittle upon contact with liquid ammonia.

Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Cleanup workers should stay upwind and keep out of low areas where ammonia vapors can accumulate. Keep away from open flames, hot surfaces and sources of ignition. Use special care to avoid static electric charges. No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe gas. If small spill, allow to vaporize or absorb vapor in water. For a large spill refer to section 5.3 for advice. Neutralization with acid is NOT recommended.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE). Persons without proper PPE should be restricted from the spill area until cleanup has been completed.

Emergency Procedures: Evacuate unnecessary personnel. Eliminate ignition sources.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Stop the flow of material, if this is without risk. Ventilate area.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Allow to vaporize or absorb the vapor in water. Use only non-sparking tools.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Do NOT enter (storage areas, confined spaces) unless adequately ventilated. Emits ammonia vapors. Flammable gas. Ammonium hydroxide reacts with many heavy metals and their salts forming explosive compounds. It attacks many metals forming flammable/explosive gas. The solution in water is a strong base, it reacts violently with acids.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Contents under pressure. The use of explosion proof equipment is recommended. Anhydrous ammonia is a product which must be handled in approved equipment and by trained personnel. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Ensure adequate ventilation. Proper grounding procedures to avoid static electricity should be followed. System design and training programs must comply with applicable regulations and in addition to good engineering practices. Pressure vessels, piping and appurtenances should be regularly inspected and tested using methods designed to reveal external and internal deterioration or defects that may impair integrity of the equipment such that an unintended release of anhydrous ammonia may result. Consult with State Department of Agriculture and other experts, as applicable, concerning methods that would be appropriate given the particular circumstances. Refer to 29 CFR 1910.111 Storage and Handling of Anhydrous Ammonia, 29 CFR 1910.119 Process Safety Management of Highly Hazardous Materials and the current ANSI standard K61.1, Safety Requirements for the Storage and Handling of Anhydrous Ammonia for additional information.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep in fireproof place. Store locked up. Storage containers should have safety relief valves. Note that many materials, particularly plastics, become brittle upon contact with liquid ammonia.

Incompatible Materials: Strong bases. Strong oxidizers. strong acids. Metals. Metal salts. Organic materials. Hypochlorites.

Storage Area: Post readily visible warning signs in the storage area listing emergency measures. Water hoses should be readily available to disperse vapors in case of a spill.

7.3. Specific End Use(s) Not available

Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Ammonia (7664-41-7)		
Mexico	OEL TWA (mg/m ³)	18 mg/m ³
Mexico	OEL TWA (ppm)	25 ppm
Mexico	OEL STEL (mg/m ³)	27 mg/m ³
Mexico	OEL STEL (ppm)	35 ppm
USA ACGIH	ACGIH TWA (ppm)	25 ppm
USA ACGIH	ACGIH STEL (ppm)	35 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	35 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	18 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	27 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	35 ppm
USA IDLH	US IDLH (ppm)	300 ppm
Alberta	OEL STEL (mg/m ³)	24 mg/m ³
Alberta	OEL STEL (ppm)	35 ppm
Alberta	OEL TWA (mg/m ³)	17 mg/m ³
Alberta	OEL TWA (ppm)	25 ppm
British Columbia	OEL STEL (ppm)	35 ppm
British Columbia	OEL TWA (ppm)	25 ppm
Manitoba	OEL STEL (ppm)	35 ppm
Manitoba	OEL TWA (ppm)	25 ppm
New Brunswick	OEL STEL (mg/m ³)	24 mg/m ³
New Brunswick	OEL STEL (ppm)	35 ppm
New Brunswick	OEL TWA (mg/m ³)	17 mg/m ³
New Brunswick	OEL TWA (ppm)	25 ppm
Newfoundland & Labrador	OEL STEL (ppm)	35 ppm
Newfoundland & Labrador	OEL TWA (ppm)	25 ppm
Nova Scotia	OEL STEL (ppm)	35 ppm
Nova Scotia	OEL TWA (ppm)	25 ppm
Nunavut	OEL STEL (mg/m ³)	24 mg/m ³
Nunavut	OEL STEL (ppm)	35 ppm
Nunavut	OEL TWA (mg/m ³)	17 mg/m ³
Nunavut	OEL TWA (ppm)	25 ppm
Northwest Territories	OEL STEL (mg/m ³)	24 mg/m ³
Northwest Territories	OEL STEL (ppm)	35 ppm
Northwest Territories	OEL TWA (mg/m ³)	17 mg/m ³
Northwest Territories	OEL TWA (ppm)	25 ppm
Ontario	OEL STEL (ppm)	35 ppm
Ontario	OEL TWA (ppm)	25 ppm
Prince Edward Island	OEL STEL (ppm)	35 ppm
Prince Edward Island	OEL TWA (ppm)	25 ppm
Québec	VECD (mg/m ³)	24 mg/m ³
Québec	VECD (ppm)	35 ppm
Québec	VEMP (mg/m ³)	17 mg/m ³
Québec	VEMP (ppm)	25 ppm

Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Saskatchewan	OEL STEL (ppm)	35 ppm
Saskatchewan	OEL TWA (ppm)	25 ppm
Yukon	OEL STEL (mg/m ³)	30 mg/m ³
Yukon	OEL STEL (ppm)	40 ppm
Yukon	OEL TWA (mg/m ³)	18 mg/m ³
Yukon	OEL TWA (ppm)	25 ppm

8.2. Exposure Controls

Appropriate Engineering Controls: Gas detectors should be used when flammable gases/vapors may be released. Gas detectors should be used when toxic gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use explosion-proof equipment. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection. Face shield.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Thermal Hazard Protection: Wear cold insulating gloves.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Gas
Appearance	: Colorless liquid or gas
Odor	: Pungent odor considered suffocating
Odor Threshold	: 1 - 50 ppm in humans
pH	: 10.6 - 11.6 (0.02-1.7% aqueous ammonia solution)
Evaporation Rate	: Not available
Melting Point	: -108 °F (- 77 °C)
Freezing Point	: Not available
Boiling Point	: -28.1 °F (- 33.4 °C)
Flash Point	: Not available
Auto-ignition Temperature	: 1,204 °F (651 °C)
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: 16 % (by volume in air)
Upper Flammable Limit	: 25 % (by volume in air)
Vapor Pressure	: 8.5 atm at 68°F (20°C)
Relative Vapor Density at 20 °C	: 0.597 (at 32°F and 760 mmHg) (lighter than air)
Relative Density	: Not available
Specific Gravity	: 0.62 at 60°F (16°C)
Solubility	: Soluble in water. Water: 51 g at 68°F (20°C)
Partition Coefficient: N-Octanol/Water	: - 1.14 at 68°F (25°C)
Viscosity	: 0.475 cP at -92°F (-69°C)
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Corrosive to copper and aluminum, including their alloys, and galvanized surfaces.
- 10.2. **Chemical Stability:** Flammable gas. Contains gas under pressure; may explode if heated. Can form explosive mixture with air.
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.
- 10.5. **Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Metals. Organic materials. Hypochlorites. Metal salts.
- 10.6. **Hazardous Decomposition Products:** Nitrogen oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity: Inhalation:gas: Toxic if inhaled.

LD50 and LC50 Data:

Anhydrous Ammonia (7664-41-7)	
ATE US (gases)	2,000.10 ppmV/4h

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

pH: 10.6 - 11.6 (0.02-1.7% aqueous ammonia solution)

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 10.6 - 11.6 (0.02-1.7% aqueous ammonia solution)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Toxic if inhaled.

Symptoms/Injuries After Skin Contact: Corrosive. Causes burns. Symptoms may include: Redness. Pain. Serious skin burns. Blisters.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva. Redness. Pain. Blurred vision. Severe burns.

Symptoms/Injuries After Ingestion: Ingestion is an unlikely route of exposure for a gas.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Ammonium hydroxide (1336-21-6)	
LD50 Oral Rat	350 mg/kg
Ammonia (7664-41-7)	
LC50 Inhalation Rat	5.1 mg/l (Exposure time: 1 h)
LC50 Inhalation Rat	2000 ppm/4h (Exposure time: 4 h)

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Toxic to aquatic life with long lasting effects. Very toxic to aquatic life.

Ammonium hydroxide (1336-21-6)	
LC50 Fish 1	8.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.66 mg/l (Exposure time: 48 h - Species: water flea)
EC50 Daphnia 2	0.66 mg/l (Exposure time: 48 h - Species: Daphnia pulex)
Ammonia (7664-41-7)	
LC50 Fish 1	0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio)
EC50 Daphnia 1	25.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	0.26 - 4.6 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

12.2. Persistence and Degradability

Anhydrous Ammonia (7664-41-7)	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Anhydrous Ammonia (7664-41-7)	
Bioaccumulative Potential	Not established.

Ammonia (7664-41-7)	
Log Pow	-1.14 (at 25 °C)

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable. Prevent runoff from entering drains, sewers or waterways.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT

Proper Shipping Name : AMMONIA, ANHYDROUS
Hazard Class : 2.2
Identification Number : UN1005
Label Codes : 2.2
ERG Number : 125
CERCLA RQ : 100 lbs



14.2. In Accordance with IMDG

Proper Shipping Name : AMMONIA, ANHYDROUS
Hazard Class : 2
Identification Number : UN1005
Label Codes : 2.3,8
EmS-No. (Fire) : F-C
EmS-No. (Spillage) : S-U



14.3. In Accordance with IATA

Proper Shipping Name : AMMONIA, ANHYDROUS
Identification Number : UN1005
Hazard Class : 2
Label Codes : 2.3,8
ERG Code (IATA) : 2CP



14.4. In Accordance with TDG

Proper Shipping Name : ANHYDROUS AMMONIA
Hazard Class : 2.3
Identification Number : UN1005
Label Codes : 2.3,8
ERP : >3000 L



Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Anhydrous Ammonia (7664-41-7)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Sudden release of pressure hazard
Ammonium hydroxide (1336-21-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Ammonia (7664-41-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard
SARA Section 313 - Emission Reporting	1.0 % (includes anhydrous Ammonia and aqueous Ammonia from water dissociable Ammonium salts and other sources, 10% of total aqueous Ammonia is reportable under this listing)

15.2. US State Regulations

Ammonium hydroxide (1336-21-6)	
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities	
U.S. - Louisiana - Reportable Quantity List for Pollutants	
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1	
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2	
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity	
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1	
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2	
RTK - U.S. - Massachusetts - Right To Know List	
U.S. - Massachusetts - Toxics Use Reduction Act	
U.S. - Michigan - Polluting Materials List	
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances	
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - New Jersey - Special Health Hazards Substances List	
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)	
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances	
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Ammonia (7664-41-7)	
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute	
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic	
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)	
U.S. - Connecticut - Water Quality Standards - Acute Freshwater Aquatic Life Criteria	
U.S. - Connecticut - Water Quality Standards - Acute Saltwater Aquatic Life Criteria	
U.S. - Connecticut - Water Quality Standards - Chronic Freshwater Aquatic Life Criteria	
U.S. - Connecticut - Water Quality Standards - Chronic Saltwater Aquatic Life Criteria	
U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities	

Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities
U.S. - Delaware - Accidental Release Prevention Regulations - Toxic Endpoints
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Florida - Essential Chemicals List
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Criteria Pollutants
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Polluting Materials List
U.S. - Michigan - Process Safety Management Highly Hazardous Chemicals
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New Mexico - Precursor Chemicals
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Carolina - Control of Toxic Air Pollutants
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Ohio - Accidental Release Prevention - Threshold Quantities
U.S. - Ohio - Extremely Hazardous Substances - Threshold Quantities
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Oregon - Precursor Chemicals
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Rhode Island - Water Quality Standards - Acute Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Acute Saltwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Chronic Freshwater Aquatic Life Criteria
U.S. - Rhode Island - Water Quality Standards - Chronic Saltwater Aquatic Life Criteria
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Texas - Effects Screening Levels - Long Term

Anhydrous Ammonia

Safety Data Sheet


According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Texas - Effects Screening Levels - Short Term
 U.S. - Vermont - Permissible Exposure Limits - STELs
 U.S. - Virginia - Water Quality Standards - Acute Freshwater Aquatic Life
 U.S. - Virginia - Water Quality Standards - Acute Saltwater Aquatic Life
 U.S. - Virginia - Water Quality Standards - Chronic Freshwater Aquatic Life
 U.S. - Virginia - Water Quality Standards - Chronic Saltwater Aquatic Life
 U.S. - Virginia - Water Quality Standards - Public Water Supply Effluent Limits
 U.S. - Virginia - Water Quality Standards - Surface Waters Not Used for the Public Water Supply Effluent Limits
 U.S. - Washington - Permissible Exposure Limits - STELs
 U.S. - Washington - Permissible Exposure Limits - TWAs
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
 U.S. - Wyoming - Process Safety Management - Highly Hazardous Chemicals
 U.S. - Alaska - Water Quality Standards - Acute Aquatic Life Criteria for Fresh Water
 U.S. - Alaska - Water Quality Standards - Chronic Aquatic Life Criteria for Fresh Water
 U.S. - Alaska - Water Quality Standards - Acute Aquatic Life Criteria for Marine Water
 U.S. - Alaska - Water Quality Standards - Chronic Aquatic Life Criteria for Marine Water
 U.S. - Alaska - Ambient Air Quality Standards

15.3. Canadian Regulations

Anhydrous Ammonia (7664-41-7)

WHMIS Classification	Class E - Corrosive Material Class B - Flammable Gas Class A - Compressed Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects
----------------------	---



Ammonium hydroxide (1336-21-6)

Listed on the Canadian DSL (Domestic Substances List)
 Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class E - Corrosive Material Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Ammonia (7664-41-7)

Listed on the Canadian DSL (Domestic Substances List)
 Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material
----------------------	--

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 15 July 2015

Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Comments : This version corrects a typographical error in the header of the previous version of the SDS, which incorrectly stated that the revision date was 16 June 2015. The correct revision date was 4 June 2015.

The 4 June 2015 version contained the following revisions:

Section 1.1 Updated
Section 14.1 Updated
Section 14.4 Updated
Section 15.3 Updated


GHS Full Text Phrases:

Acute Tox. 3 (Inhalation: gas)	Acute toxicity (inhalation: gas) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Gas 2	Flammable gases Category 2
Liquefied gas	Gases under pressure Liquefied gas
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H221	Flammable gas
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA Fire Hazard : 1 - Must be preheated before ignition can occur.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

Party Responsible for the Preparation of This Document

CF Industries, Corporate EHS Department, 847-405-2400

Anhydrous Ammonia

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

CF believes the information contained herein is accurate; however, CF makes no guarantees or warranties with respect to such accuracy and assumes no liability in connection with the use of the information contained herein by any party. The provision of the information contained herein by CF is not intended to be and should not be construed as legal advice or as ensuring compliance by other parties. Judgments as to the suitability of the information contained herein for the party's own use or purposes are solely the responsibility of that party. Any party handling, transferring, transporting, storing, applying or otherwise using this product should review thoroughly all applicable laws, rules, regulations, standards and good engineering practices. Such thorough review should occur before the party handles, transfers, transports, stores, applies or otherwise uses this product.

North America GHS US 2012 & WHMIS 2